



AquaPure™ DW-14

Aquapure DW-14 is a high charge density, organic cationic coagulant formulated for use in systems for dewatering where liquid/solid separation is required or where oil and grease are the main contaminants. It works well to break emulsions. It is compatible with most systems and can be metered in for easy dosing. Dosages range from 100 ppm to 1,000 ppm depending on the system design loading and mixing action.

Aquapure DW-14 works well over a wide pH range and can be used alone or with other organic coagulants in conjunction with diatomaceous earth or bentonite clay.

Features & Benefits

Organic coagulant	Helps clear up “hazy” effluent
Liquid ready to use	Easy to meter into systems
Demulsifies oils	Great for food processing waste streams

Physical Data

pH	5.0 – 7.0
Viscosity	1,000 – 3,000
Color	Straw colored
Specific gravity	1.04

Typical Applications

- Dewatering of liquid/solid phase
- Used for decolonization, algae, & removes inorganics and organics
- Acts to aid in sweep flocculation

Caution

Do not Freeze



WARRANTY: THE QUALITY OF THIS PRODUCT IS GUARANTEED ON SHIPMENT FROM OUR PLANT. IF THE USE RECOMMENDATIONS ARE FOLLOWED, DESIRED RESULTS WILL BE OBTAINED. SINCE THE USE OF OUR PRODUCTS IS BEYOND OUR CONTROL, NO GUARANTEE EXPRESSED OR IMPLIED IS MADE AS TO THE EFFECTS OF SUCH USE, OR THE RESULTS TO BE OBTAINED.

Our People. Your Problem Solvers.

For more information on this process,
please call us at 203.756.5521 or email: techservice@hubbardhall.com

Hubbard-Hall holds certifications for **ISO 9001:2015**, Responsible Distribution, as accredited by the **ACD** (Alliance for Chemical Distributors) and as a **Women-Owned Small Business**, as well as maintaining an association with **Omni-Chem**¹³⁶.